

www.chainandcable.com



INDUSTRIAL
QUALITY AND PERFORMANCE.

ICC® Grade 30 Chain



A general purpose chain for all ordinary applications requiring superior corrosion resistance, second only to stainless steel. This hot dipped galvanized chain is particularly suitable for marine environments.

PROOF COIL

Part #	Description	Working Load Limit	Feet per Half Drum	Weight per Foot
14PCHDG	1/4"	1,250	400	0.6
516PCHDG	5/16"	1,900	275	0.81
38PCHDG	3/8"	2,650	200	1.42
12PCHDG	1/2"	4,500	100	2.78

ICC® Grade 43 Chain



A higher strength carbon steel provides an increased strength to weight ratio plus resistance to wear and abrasion. Industrial applications include lumbering, construction, binding and load securement. Zinc plated.

HIGH TEST

Part #	Description	Working Load Limit	Feet per Half Drum	Weight per Foot
14HTBZ	1/4"	2,600	400	.66
516HTBZ	5/16"	3,900	275	.83
38HTBZ	3/8"	5,400	200	1.42
12HTBZ	1/2"	9,200	100	2.36

ICC® Grade 70 Chain



Load ratings for grade 70 transport chain average 20% higher than grade 43, so a smaller size chain can be used for many jobs. Primarily for load binding in the transportation industry, it is also used extensively on farms, in lumbering, towing and construction. Yellow Dichromate finish.

TRANSPORT

Part #	Description	Working Load Limit	Feet per Half Drum	Weight per Foot
14T	1/4"	3,150	400	.62
516T	5/16"	4,700	275	1.02
38T	3/8"	6,600	200	1.36
12T	1/2"	11,300	100	2.44

ICC® Grade 70 Weld-On Hook



ICC® Grade 70
Weld-On Hook

WELD-ON HOOK

Part #	Description	Type	Weight
90300i	5/16"	Weld-On	.39
90304i	3/8"	Weld-On	.90
90305i	1/2"	Weld-On	1.3

ICC® Grade 43 Hooks



grab



slip

These hot forged, heat treated and tempered hooks attach directly to welded chain with no connecting links to buy. They have a clear protective finish to resist rust and for cleaner handling. Made for use on all high test chain (grade 43).

HIGH TEST

Part #	Description	Working Load Limit	Weight
M804Li	1/4" Grab	2,600	.43
M904Li	1/4" Slip	2,600	.61
M805Li	5/16" Grab	3,900	.72
M905Li	5/16" Slip	3,900	.93
M806Li	3/8" Grab	5,400	1.05
M906Li	3/8" Slip	5,400	1.36
M808Li	1/2" Grab	9,200	2.31
M908Li	1/2" Slip	9,200	2.85

ICC® Grade 70 Hooks



grab



slip

Designed specifically for Grade 70 Transport chain with matching Working Load Limits. Higher strength-to-weight ratios than grade 43 hooks.

TRANSPORT

Part #	Description	Working Load Limit	Weight
M804Ti	1/4" Grab	3,150	.41
M904Ti	1/4" Slip	3,150	.59
M805Ti	5/16" Grab	4,700	.75
M905Ti	5/16" Slip	4,700	.88
M806Ti	3/8" Grab	6,600	1.66
M906Ti	3/8" Slip	6,600	1.32
M808Ti	1/2" Grab	11,300	2.33
M908Ti	1/2" Slip	11,300	2.94

ICC® Commercial Shackles

Our ICC® commercial grade shackles are an economical choice for a variety of applications. Available in galvanized finish.



COMMERCIAL

Part #	Description	Weight
646001	1/4"	.07
647001	5/16"	.14
648001	3/8"	.28
649001	7/16"	.50
650001	1/2"	.63
651001	5/8"	1.12
652001	3/4"	2.29

BABAC® Load Rated Shackles

Offering BABAC® Black™ Pin Load Rated Shackles by feature oversized threaded pins and easy-to-read size and working load limit (in tons) on each piece. Not recommended for overhead lifting.



TRANSPORT

Part #	Description	Working Load Limit	Weight
646B	1/4"	.50 Tons	.12
647B	5/16"	.75 Tons	.18
648B	3/8"	1.00 Tons	.33
649B	7/16"	1.50 Tons	.44
650B	1/2"	2.00 Tons	.70
651B	5/8"	3.25 Tons	1.24
652B	3/4"	4.75 Tons	2.22
653B	7/8"	6.50 Tons	3.63
654B	1"	8.50 Tons	5.12

QUALITY AND PERFORMANCE YOU CAN TRUST



INTERNATIONAL
CHAIN AND CABLE



ICC® Load Binders



Factory tested for dependability. Designed to prevent the clevis from separating from handle of binder. Manufactured for the long-haul, these binders bring additional features to the road.

LEVER LOAD BINDER

Part #	Description	Working Load Limit	Weight
WRF225I	1/4" Lever	2,200	3.42
BX320I	5/16" - 3/8" Lever	5,400	7.88



Turnbuckle style ratchet binder offers all steel construction, drop forged steel components, Acme threaded screws, rust proofed, spring loaded pawls. Made to bind difficult loads such as industrial machinery, steel erection, etc.

RATCHET LOAD BINDER

Part #	Description	Working Load Limit	Weight
BXR310i	5/16" - 3/8" Ratchet	6,600	10.19
BXR410i	3/8" - 1/2" Ratchet	9,200	11.79
BXR510i	1/2" - 5/8" Ratchet	13,000	14.4

ICC® Binder Chain




Used by truckers, contractors, oil field crews and farmers. Clevis grab hook on each end of grade 70 binder chain. Yellow Dichromate finish.

BINDER CHAIN

Part #	Description	Packaged Quantity	Weight per Piece
51616Ti	5/16" x 16' G70	25	17
51620Ti	5/16" x 20' G70	25	20
3816Ti	3/8" x 16' G70	25	24
3820Ti	3/8" x 20' G70	25	29

Premium Webbing



Premium quality polyester webbing for maximum strength, durability and wear resistance. Each assembly has a heavy duty ratchet mechanism.

RATCHET ASSEMBLIES

Part #	Description	Capacity	Weight
SA10X27i	2x27' Flat Hook	10,000	6.7
SA10X30i	2x30' Flat Hook	10,000	7.0



flat hook

Premium quality polyester webbing for maximum strength, durability and wear resistance.

WINCH STRAPS

Part #	Description	Capacity	Weight
FH2X27i	2x27' Flat Hook	10,000	2.7
FH2X30i	2x30' Flat Hook	10,000	3.2




RATCHET STRAPS

Part #	Description	Weight
R312SI	1x12' Ratchet Assembly W/S Hooks	1.76
R315SI	1x15' Ratchet Assembly W/S Hooks	1.87



ICC® Wire Rope



Commonly used for winch lines, General Purpose wire rope is also used in industrial, agricultural, marine and consumer applications.

ICC® 6 X 26 IWRC EIPS GENERAL PURPOSE WIRE ROPE

Part #	Description	Breaking Strength	Weight per Foot
14i	1/4"	3.40 tons	.12
516i	5/16"	5.27 tons	.18
38i	3/8"	7.55 tons	.26
716i	7/16"	10.22 tons	.35
12i	1/2"	13.30 tons	.46
916i	9/16"	16.80 tons	.59
58i	5/8"	20.60 tons	.72
34i	3/4"	29.40 tons	1.04
78i	7/8"	39.80 tons	1.42
1i	1"	51.70 tons	1.85



Aircraft Galvanized wire rope has a wide variety of uses. Wire is coated to protect against corrosion.

ICC® AIRCRAFT GALVANIZED

Part #	Description	Breaking Strength	Weight per 500'
18500GAC	1/8" x 500'	1.00 tons	35
316500GAC	3/16" x 500'	2.10 tons	30
14500GAC	1/4" x 500'	3.50 tons	68.0
516500GAC	5/16" x 500"	4.90 tons	99.5
38500GAC	3/8" x 500'	7.20 tons	134.5



ACCESSORIES



Quick Links
1/8" to 1/2"



Cable Clamps



Thimbles



Wedge Ferrule Assemblies 1/2" to 3/4"



Hydraulic Wire Rope Cutter



Cable Cutter and Blades



YOUR LOCAL DEALER

www.chainandcable.com

International Chain and Cable is a division of Wallingford's Inc.



MARKETED WORLDWIDE by

Wallingford's Inc.
1010 Kennedy Memorial Drive
Oakland, ME USA 04963

207 465 9575 | 800 323 3708
Fax: 207 465 9601

www.wallingfords.com
info@wallingfords.com



WALLINGFORD'S INC.